## Product data sheet

DOWNTOWN NO TRIM Ø215 03.0457/TC-TEL/42W


FLOS





Luminaires for embedded installation indoor with fluorescent lamps and of halogenuro metalist. Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.

Light output 1



| $\neg$             |                                    | 444 | H                  |
|--------------------|------------------------------------|-----|--------------------|
|                    |                                    |     |                    |
| T                  | $\times / \square$                 |     | T                  |
| $\langle \rangle$  | $\langle \rangle \not \rightarrow$ | +   | $\bigtriangledown$ |
| $\times$           |                                    | t   | $\sim$             |
| $\bigtriangledown$ |                                    | P   | $\checkmark$       |
| $\checkmark$       |                                    |     | 7                  |
| 1                  |                                    | 1   |                    |

## 1 x Compact fluorescent lamp

| Nominal lamp power | 42 W    | Socket      | Gx24Q-4 |
|--------------------|---------|-------------|---------|
| Lamp flux          | 3200 lm | LOR         | 49%     |
| Luminous efficacy  | 38 lm/W | Total flux  | 1577 lm |
| CCT                | 4000 K  | Total power | 42 W    |
| CRI                | 79      |             |         |
|                    |         |             |         |

| 1 x Compact fluorescent lamp |  |
|------------------------------|--|
|------------------------------|--|

| Nominal lamp power | 42 W    | Socket      | Gx24Q-4 |
|--------------------|---------|-------------|---------|
| Lamp flux          | 3200 lm | LOR         | 49%     |
| Luminous efficacy  | 38 lm/W | Total flux  | 1577 lm |
| CCT                | 3000 K  | Total power | 42 W    |
| CRI                | 84      |             |         |
|                    |         |             |         |

| Mounting mode          | Electric           |  |
|------------------------|--------------------|--|
| Ceiling recessed       | System power: 42 W |  |
| Shape and measurements | Protection         |  |
| Height: 8.46 in        | IP: 23             |  |
| Diameter: 8.46 in      |                    |  |

## Adjustability

Fixed