


Product data sheet

STANDARD
50400.380
RZB



IP
44

IK
07

Series: Standard Type of Protection: IP 44 Protection Class: II Voltage: - 250 / 0 - 60 Hz Base: plastic. Two cable inlets. Cover: textured glass, transparent. Protective cage: steel wire, "galvanised; screw mounting. Regional version for Denmark." Available Colours: grey Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 193, B 132, H 117 Lamp: 1 x E27 max. 60 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Beam Angle: 90°/90°/62°/90° Unified Glare Ratio: 26,1 EEC: A++ - E

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	12 W	Socket	E27
Lamp flux	725 lm	LOR	72%
Luminous efficacy	43 lm/W	ULOR	17%
CCT	2700 K	Total flux	519 lm
CRI	80	Total power	12 W

Mounting mode

Wall mounted

Shape and measurements

Length: 5.20 in
Width: 7.60 in
Height: 4.33 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 44
IK: 07