


# Product data sheet

FACET D/I 44W 3000K RA>80 CD-SD/I LENS C  
8246093394  
SG ARMATUREN



Facet is a high performance luminaire suitable for office or school lighting. The slim design is available with direct or direct/indirect light distribution. Optic based on micro prism optics. Energy efficiency - up to 128 lm/W Available with non-dim and dimmable DALI/Switch&Dim Slim design No harsh glare of multiple diodes Plug and play Available with pull-switch Light distribution Direct or Direct/Indirect Light source LED 19W, 27W, 37W, 44W 3000K or 4000K Ra>80 SDCM:3 Control gear On/Off Switch&Dim Intern On/Off Emergency 3H DALI DALI Emergency 3H Protection Class I, IP20, Ta=25°C, CE Optics Direct and Direct/Indirect. Direct: Prismatic optic - PMMA Indirect: Clear PC Material and Finish Housing: Sheet steel powder coated white RAL9010/25. Lens optic in PMMA and PC. Endcaps in ABS Mounting/Connection Wire suspended. Adjustable wire suspensions included (2x2.0m). (Ceiling fixing kit to be ordered separately). Cable entry on top of luminaire. Pre-wired with cable (2.5m). Fixing points 1000mm. How to specify Suspended direct or direct/indirect, in 3000 or 4000 Kelvin LED. Slim profile luminaire, sheet steel construction, ABS endcaps, finished in white - with anti-glare micro prism optic, complete with electronic driver for none dim and DALI/Switch&Dim, including 2.5 metre cable, 2 metre wire suspensions. As Riegens Facet range.

## Light output 1



1 x LED			
Nominal lamp power	44 W	LOR	100%
Lamp flux	5100 lm	ULOR	47%
Luminous efficacy	116 lm/W	Total flux	5096 lm
CCT	3000 K	Total power	44 W
CRI	80		

## Mounting mode

Pendant

## Shape and measurements

Length: 59.61 in

Width: 2.52 in

Height: 3.94 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 44 W

Appliance Class: II

## Protection

IP: 20