
Product data sheet

PLANOX TUBE 601069.002.1

RZB








Series: Planox Tube Type of Protection: IP 67 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz End caps: grey plastic (polyamide). Diffuser: shock resistant opal plastic (polycarbonate). One cable inlet with through wiring. Integrated converter. LED included. Available Colours: white Type of Installation: universal mounting system Dimensions: D 78, L 1530, Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: D-mark, F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 6600lm System power: 55W Beam Angle: 135°/103° Number of fittings B10A: 11 Number of fittings B16A: 19 Number of fittings C10A: 19 Number of fittings C16A: 32 Inrush current: 32A Unified Glare Ratio: 26,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	55 W	CRI	80
Total flux	6600 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	12%
		Total power	55 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.07 in Width: 60.24 in Height: 2.95 in

Adjustability

Fixed

Electric

System power: 55 W

Protection

IP: 67 IK: 10