

Product data sheet


GLASSGLASS
D31 P/1
LUCEPLAN



IP
20


La versatilità di un sistema componibile e l'eleganza del pezzo unico. La struttura a maniglia in alluminio pressofuso sostiene con sicurezza una serie di vetri diffusori realizzati secondo le antiche tradizioni della soffiatura. Il cavo elettrico, ingabbiato in una maglia di acciaio, è portante.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	205 W	Socket	E27
Lamp flux	2520 lm	LOR	98%
Luminous efficacy	10 lm/W	ULOR	26%
CCT	2821 K	Total flux	2480 lm
CRI	99	Total power	250 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	140 W	Socket	E27
Lamp flux	2840 lm	LOR	98%
Luminous efficacy	11 lm/W	ULOR	26%
CCT	3000 K	Total flux	2795 lm
CRI	99	Total power	250 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	105 W	Socket	E27
Lamp flux	1980 lm	LOR	98%
Luminous efficacy	8 lm/W	ULOR	26%
CCT	3000 K	Total flux	1949 lm
CRI	99	Total power	250 W

Mounting mode

Pendant

Electric

System power: 250 W

Shape and measurements

Length: 13.56 in

Width: 13.56 in

Height: 20.12 in

Adjustability

Height adjustable

Protection

IP: 20