

# Product data sheet

NADJA V (2-ARMED)  
9.871.1052.85  
LEIPZIGER LEUCHTEN



IP  
55


Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	100 W	LOR	77%
Lamp flux	10000 lm	Total flux	7717 lm
Luminous efficacy	67 lm/W	Total power	115 W
CCT	3000 K		
CRI	90		

## Light output 2



1 x Metal halide lamp			
Nominal lamp power	100 W	LOR	77%
Lamp flux	10000 lm	Total flux	7717 lm
Luminous efficacy	67 lm/W	Total power	115 W
CCT	3000 K		
CRI	90		

## Mounting mode

Pole top mounted

## Electric

System power: 230 W

## Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

## Protection

IP: 55