



# Product data sheet

I-BRICK/2 - CVDA  
6001-0-7-681-XX  
UNILAMP



Description I-BRICK is a range of wall recessed luminaires with LED light sources. The glare-free cover enables I-BRICK to be installed in most places where a comfortable illumination is needed. The high quality LED chip from world renowned manufacturers allow for less energy consumption with acceptable lighting levels. I-BRICK family is available in 5 different front covers in 2 sizes. The shallow housing can be installed in either wall or step where recess depth is limited. The high quality LED driver is integrated inside the luminaire for ease of installation. They are widely used to illuminate stairways, pathways and walls. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-2 and VDE regulations. • LM6 die-cast aluminium body. • GFR polymer recess box. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate or Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x LED			
Nominal lamp power	3.9 W	LOR	19%
Lamp flux	530 lm	Total flux	101 lm
Luminous efficacy	136 lm/W	Total power	3.9 W
CCT	3000 K		
CRI	80		

## Mounting mode

Wall recessed

## Shape and measurements

Length: 9.76 in  
Width: 4.52 in  
Height: 3.23 in

## Adjustability

Fixed

## Electric

System power: 3.9 W  
Controller: DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 06