



Product data sheet

FLD111 [EE] IP66:LED-3/6W/4K
145-9823
WE-EF



IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Including terminal box, for mounting on \varnothing 48-60 mm pipes or space frames.

Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 3 x LED | | | |
| Nominal lamp power | 2 W | LOR | 75% |
| Lamp flux | 310 lm | Total flux | 694 lm |
| Luminous efficacy | 93 lm/W | Total power | 7.5 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

Mounting mode

Standing / Bollard

Shape and measurements

Length: 3.74 in
Width: 3.74 in
Height: 2.17 in
Weight: 2.4 kg

Electric

System power: 7.5 W
Appliance Class: I

Protection

IP: 66
IK: 07