


Product data sheet

CALLISTO WALL BLACK 110LM 3000K RA>80 TRAILING EDGE DIMMING
7021989140153
SG ARMATUREN



Good little LED luminaire for walls and ceiling. For both outdoor and indoor use. Well integrated LED chip, dimmable via phase-dimming. Made of die-cast powder-coated aluminium, powder coating and 10-year corrosion warranty, glass diffuser. 33 cm in total height, KL II means that it can be mounted without earthing, direct 230 V with loopable quick clips. Light distribution Direct/Asymmetric Light technic LED (not exchangeable) 3W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK06 Energy and approvals CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 115, B16: 184, C10: 134, C16: 215

Light output 1



1 x LED			
Nominal lamp power	3 W	LOR	100%
Lamp flux	110 lm	Total flux	110 lm
Luminous efficacy	37 lm/W	Total power	3 W
CCT	3000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.33 in
Width: 1.06 in
Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 3 W
Appliance Class: II

Protection

IP: 65
IK: 06