


Product data sheet

1M RT 2-5000 24V RGBW-ONE DAY 2X (5060, 300 LED, LUX)
019151
ARLIGHT RUS LLC




Гибкая лента LUX, светодиоды smd 5060 RGBW 4-в-1, 60шт/м Цвет RGB + Дневной 3800-4200K. Питание 24V, мощность 4.8 Вт/м на канал R/G/B/W, общая 19.2 Вт/м Угол 120°, цветопередача CRI>85. Размеры 5000x12x2.2мм. Мин.отрезок 100мм, 6шт светодиодов. Рекомендуется установка на профиль.


Light output 1




1 x LED			
Nominal lamp power	3.7 W	LOR	100%
Lamp flux	340 lm	Total flux	340 lm
Luminous efficacy	92 lm/W	Total power	3.7 W
CCT	4087 K		
CRI	84		



1 x LED			
Nominal lamp power	3.9 W	LOR	100%
Lamp flux	99 lm	Total flux	99 lm
Luminous efficacy	25 lm/W	Total power	3.9 W
CCT	0 K		
CRI	-29		



1 x LED			
Nominal lamp power	4.3 W	LOR	100%
Lamp flux	247 lm	Total flux	247 lm
Luminous efficacy	57 lm/W	Total power	4.3 W
CCT	0 K		
CRI	-18		



1 x LED			
Nominal lamp power	4 W	LOR	100%
Lamp flux	73 lm	Total flux	73 lm
Luminous efficacy	13 lm/W	Total power	4 W
CCT	0 K		
CRI	-50		

Mounting mode

Ceiling mounted

Electric

System power: 3.7-4.3 W

Shape and measurements

Length: 39.37 in

Width: 0.47 in

Height: 0.12 in

Protection

IP: 33

Adjustability

Fixed