


Product data sheet

MINI RETINA-4
7047-0-5-805-XX
UNILAMP



Description RETINA is a round wall/ceiling light with robust aluminium construction and impact resistant polycarbonate lens cover. It utilizes a high quality mid-power SMD LED module. RETINA is also available with built-in microwave sensor and hi-low light function. The high protection rating of IP65 and IK09 allows RETINA to be installed in most outdoor environments. With a diffused light distribution, it provides general lighting in private and public areas and is perfect for commercial use. The front cover is available in various designs; moreover, RETINA is available in 2 sizes with the choice of 5 different colours. • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. Replaceable for future upgrade. • Optional with motion detector (Microwave Sensor). • Quick connector for easy installation. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



| | | | |
|--------------------|----------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 11 W | LOR | 62% |
| Lamp flux | 1130 lm | Total flux | 704 lm |
| Luminous efficacy | 103 lm/W | Total power | 12 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

Mounting mode

Wall mounted

Shape and measurements

Length: 10.32 in
Width: 4.72 in
Height: 10.32 in

Adjustability

Fixed

Electric

System power: 12 W
Controller: DALI
Appliance Class: I

Protection

IP: 65
IK: 09