

Product data sheet

FLAT POLYMERO ALU
311647.002.1
RZB



IP
43

IK
03

Series: Flat Polymero Alu Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Mounting support body die-cast aluminium powder-coated, cover mounted with bayonet mounting, cover plastic (PMMA), opal, lamps (LED) included in delivery. IP43 ceiling mounting, IP44 wall mounting. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 350, H 130 Lamp: LED Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1300lm System power: 21W Beam Angle: 122° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 19,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	21 W	CRI	80
Total flux	1300 lm	LOR	100%
Luminous efficacy	62 lm/W	ULOR	13%
		Total power	21 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.12 in
Diameter: 13.78 in

Adjustability

Fixed

Electric

System power: 21 W

Protection

IP: 43
IK: 03