


# Product data sheet

PURA SPOT R MAXI  
911349.002  
RZB




Series: Pura Spot R Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 65° vertically, spring fastening with no need for tools, heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools, passive cooling. LED included together with connected converter in separate gearbox. Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Recessed ceiling mounting Dimensions: L 360, B 180, H 50, HE 120 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3100K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4600lm System power: 54W Beam Angle: 15° Number of fittings B10A: 7 Number of fittings B16A: 12 Inrush current: 32A Unified Glare Ratio: 17,3 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	27 W	CRI	90
Total flux	2300 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	27 W

## Light output 2 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	27 W	CRI	90
Total flux	2300 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	27 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 7.09 in  
Width: 14.17 in  
Height: 6.06 in

## Electric

System power: 54 W

## Protection

IP: 20  
IK: 03

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: White