Product data sheet

NADJA II (2-ARMED) 9.874.2072.05

LEIPZIGER LEUCHTEN








Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	150 W	
Lamp flux	17000 lm	
Luminous efficacy	75 lm/W	
CCT	2000 K	
CRI	25	

LOR 77%
Total flux 13118 lm
Total power 176 W

Light output 2



1 x High pressure sodium vapour lamp			
Nominal lamp power	150 W	LOR	
Lamp flux	17000 lm	Total flux	
Luminous efficacy	75 lm/W	Total power	
CCT	2000 K		
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in Electric

System power: 352 W

Protection

IP: 55

77% 13118 lm 176 W