


# Product data sheet

LIGHT LINEAR VT 2 BOLLARDS  
VT-10012-T2-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	52.9 W	CRI	80
Total flux	5286 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	20%
		Total power	52.9 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	52.9 W	CRI	80
Total flux	5286 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	20%
		Total power	52.9 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 4.88 in  
Width: 7.87 in  
Height: 39.37 in  
Weight: 9.9 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 105.8 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 07

Surface temperature: 40°C