


# Product data sheet

KIPP BOLLARD, LED 28W / 4000K  
5747813319  
LOUIS POULSEN



Kipp Bollard Design : Alfred Homann Concept : The fixture emits symmetrical light directed downward. The relation between the slightly curved top shade and the angle of the inner opal diffuser ensures a wide non glare light distribution. Finish : Aluminium coloured with textured surface or graphite grey, powder coated. Material : Diffuser: Injection moulded white opal acrylic. Top shade: Die cast aluminium. Enclosure: Injection moulded clear polycarbonate. Frame: Die cast aluminium. Post: Extruded aluminium. Mounting : Access door: Yes. Terminal block positioning: In post. Looping: Approved, max 5x6mm<sup>2</sup>. Ballast positioning: In pole top. Max. installation cable: Electric shock protection I: 1 or 2 pcs. 5x6mm<sup>2</sup> or Electric shock protection II: 1 or 2 pcs 4x6mm<sup>2</sup>. Post f/in-ground installation: H: 1705mm excl. fixture head, in-ground part: 600mm. Post w/base plate for surface mounting: H: 1105mm excl. fixture head. Post dia. 115mm. Class : Ingress protection IP55. Electric shock protection I w. ground, II w/o ground. Vandal Proof II. Weight : Max. 20kg.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	1523 lm	LOR	100%
Luminous efficacy	54 lm/W	ULOR	10%
		Total power	28 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 43.50 in

Diameter: 17.32 in

## Adjustability

Fixed

## Electric

System power: 28 W

Appliance Class: II

## Protection

IP: 55

IK: 10