

Product data sheet

SCAPHA
311991.004.1
RZB



IP
20

Series: Scapha Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: aluminium, powder-coated. Canopy and glass fixture steel powder-coated. Handmade concave glass, matt finish on the outside, painted white on the inside. Lamp (LED) included. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 1264, B 174, H 104 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 3550lm System power: 51W Beam Angle: 154°/113° Number of fittings B10A: 3 Number of fittings B16A: 5 Number of fittings C10A: 5 Number of fittings C16A: 9 Inrush current: 100A Unified Glare Ratio: 23,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	51 W	CRI	80
Total flux	3550 lm	LOR	100%
Luminous efficacy	70 lm/W	ULOR	11%
		Total power	51 W

Mounting mode

Wall mounted

Electric

System power: 51 W

Shape and measurements

Length: 6.85 in
Width: 49.76 in
Height: 4.09 in

Protection

IP: 20

Adjustability

Fixed