


# Product data sheet

SIGNALLEUCHTEN  
50608.008  
RZB




IP  
43

IK  
04

Series: Signalleuchten Type of Protection: IP 43 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: plastic, grey. Two cable inlets. Cover: plastic, coloured, glossy. Screw mounting. RZB luminaires for construction sites are labelled as follows: Signal luminaire DIN 67527-C-2-3: When mounted to a wall the lampholder must be pointing upwards (suspended lamp). Available Colours: red Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 195, B 132, H 115 Lamp: LED Life time: 32000 h (L70/B50) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK04 (0,50 Joule) Luminaire flux LED: 45lm System power: 9W Beam Angle: 180°/141° Unified Glare Ratio: 13,3 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	45 lm	LOR	100%
Luminous efficacy	5 lm/W	ULOR	27%
		Total power	9 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 5.20 in  
Width: 7.68 in  
Height: 4.53 in

## Adjustability

Fixed

## Electric

System power: 9 W

## Protection

IP: 43  
IK: 04