

Product data sheet

STICK CONE - LIGHT COLUMN


7212-0-3-780-XX

UNILAMP




STICK is a family of cylindrical-shaped light column and wall luminaire giving symmetrical light distribution on illuminated surfaces. The recommended mounting height is between 3 – 4 meters above ground. It is operated with high power LED. STICK is assembled with anti-glare suppression louvers that direct the light downward onto the illuminated surface. Clear PMMA cover protects the lamp compartment from the ingress of dust and water. It is generally installed in walkways, gardens, parks, commercial areas and open spaces to provide the general lighting from mid-high level. Anchor unit for concrete foundation are is available. spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • PMMA protective cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium louvers. • GFR PA6.6 Terminal block. • Weather proof grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	G12
Lamp flux	3300 lm	LOR	16%
Luminous efficacy	14 lm/W	Total flux	537 lm
CCT	4000 K	Total power	39 W
CRI	98		



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	G12
Lamp flux	3300 lm	LOR	16%
Luminous efficacy	14 lm/W	Total flux	537 lm
CCT	3000 K	Total power	39 W
CRI	84		

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.40 in

Width: 7.40 in

Height: 134.17 in

Electric

System power: 39 W

Appliance Class: I

Protection

IP: 65

IK: 10

Adjustability

Fixed