


Product data sheet

LIGHT LINEAR PT 2 BOLLARDS


LI-10031-T4-W40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.7 W	CRI	80
Total flux	3169 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	27.7 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.7 W	CRI	80
Total flux	3169 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	27.7 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 22.83 in

Width: 7.87 in

Height: 39.37 in

Weight: 14.9 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 55.4 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C