

# Product data sheet

VANCOUVER 2 LIGHT COLUMNS


VA-20011-W40

LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Maximum wind load resistance is 160 km/h - Surge protection 10 kV

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4032 K |
| Nominal lamp power | 21 W    | CRI         | 80     |
| Total flux         | 1414 lm | LOR         | 100%   |
| Luminous efficacy  | 67 lm/W | Total power | 21 W   |

## Mounting mode

Standing / Bollard, Pole top mounted

## Shape and measurements

Height: 118.11 in

Diameter: 6.30 in

Weight: 25 kg

## Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 21 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Protection

IP: 65

IK: 08

Surface temperature: 40°C