

# Product data sheet

VRT3 L295 UHR E3  
VERTECO3 EMERGENCY  
DEXTRA




IP  
20




Verteco 3 - IP20 Industrial Luminaire with ultra high rack optics. Steel body white powder coated paint finish and green polycarbonate end caps. Mounting to lighting trunking using standard 20mm brass bush and locknut assembly. Side entry panel mount with female power feed plug supplied. Options: E3 - Emergency control gear (1018 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R18H - Reacta 18, Daylight and Presence Detection Sensor, Narrow Lens R18W - Reacta 18, Daylight and Presence Detection Sensor, Wide Lens R18HRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Narrow Lens R18WRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Wide Lens

### Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.98 W	CRI	80
Total flux	763 lm	LOR	100%
Luminous efficacy	192 lm/W	Total power	3.98 W

### Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	179.9 W	CRI	80
Total flux	29148 lm	LOR	100%
Luminous efficacy	162 lm/W	Total power	179.9 W

### Mounting mode

Ceiling mounted, Pendant

### Shape and measurements

Length: 59.37 in  
Width: 8.46 in  
Height: 3.31 in

### Electric

System power: 183.88 W  
Ballast: ECG

### Information regarding emergency functions

Supplementary emergency lighting  
Emergency sign: N/A

## Adjustability

Fixed

## Protection

IP: 20

Designation labels: CE