

# Product data sheet

FLAT POLYMERO  
311921.002.2  
RZB




IP  
40

IK  
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base and canopy: metal, lacquered. With steel cable suspension, steplessly adjustable. Diffuser: plastic (polycarbonate). Diffuser fastening: push lock. Available Colours: white  
Type of Installation: Pendant Dimensions: D 515, H 150 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 2550lm System power: 24W Beam Angle: 114° Number of fittings B10A: 15 Number of fittings B16A: 25 Number of fittings C10A: 26 Number of fittings C16A: 42 Inrush current: 10A Unified Glare Ratio: 19,1 EEC: A++

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 24 W     | CRI         | 80     |
| Total flux         | 2550 lm  | LOR         | 100%   |
| Luminous efficacy  | 106 lm/W | ULOR        | 9%     |
|                    |          | Total power | 24 W   |

## Mounting mode

Pendant

## Electric

System power: 24 W

## Shape and measurements

Height: 5.91 in  
Diameter: 20.28 in

## Protection

IP: 40  
IK: 10

## Adjustability

Fixed