


Product data sheet

FLAT POLYMERO KREIS
672389.002.1.89
RZB




IP
40

IK
03

Item Number: 672389.002.1.89 Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, with AC Control monitoring module for Luxifair central battery units. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 360, , H 87mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Emergency Lighting System: AC-Control Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1250lm System power: 15W Beam Angle: 126° Unified Glare Ratio: 18,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.3 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	90 lm/W	ULOR	16%
		Total power	13.3 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.43 in
Diameter: 14.17 in

Adjustability

Fixed

Electric

System power: 13.3 W

Protection

IP: 40
IK: 03