Product data sheet

SIRIUS 300 - CC WALL WASHER 8033-B-5-548-XX

UNILAMP










A brand new linear light family features various mounting application types including In-ground walk over, wall mounted, wall recessed, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1



| 1 x LED |
|--------------------|
| Nominal lamp power |
| Lamp flux |
| Luminous efficacy |
| CCT |
| CRI |

| 7.1 W |
|----------|
| 900 lm |
| 127 lm/W |
| 2700 K |
| 80 |
| |

| LOR | 69% |
|-------------|--------|
| ULOR | 69% |
| Total flux | 623 lm |
| Total power | 11 W |

Mounting mode

Wall mounted

Shape and measurements

Length: 2.16 in Width: 8.29 in Height: 1.57 in

Adjustability

Free

Electric

System power: 11 W Controller: DALI Appliance Class: I

Protection

IP: 67 IK: 07