

# Product data sheet


ML4 LED 4" RECESSED DOWNLIGHT SYSTEM  
ML4D09NFL930-TIR50AWW25-TL43R2GMWWB\_TL44S2GMWWB  
COOPER LIGHTING



IP  
47

4" modular downlight; Downlight, wall wash, accent/task distributions, Field-interchangeable round and square 2-inch pinhole aperture trims, Open and lens apertures provide cutoff to source and glare control, 4 color temperatures: 2700K, 3000K, 3500K and 4000K CCT; CRI: 90, Die-formed steel trims; Magnetic attachment; Painted, plated finishes, Distributions: spot, narrow flood, flood and very wide flood, 120V-277V; Phase or 0-10V dimming down to 5%; Lumens: up to 900, L70 at 50,000 hours; D2W™ option from 3000K to 1850K, UL listed with Halo 4" housings; AIR-TITE™, ENERGY STAR™ certified; 5-year warranty

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.2 W	CRI	100
Total flux	683 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	11.2 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.39 in  
Diameter: 4.00 in

## Adjustability

Fixed

## Electric

System power: 11.2 W

## Protection

IP: 47