

Product data sheet

FLAT POLYMER0
311946.002.2.19
RZB




IP
40

IK
10

Series: FLAT POLYMER0 Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. Functional parameters of a master luminaire (ceiling height of approx. 2.8m): HF detector 24GHz with integrated corridor function. Coverage: approx. 130° radial. Easy adjustment of functions via associated push button switches. Sensitivity/Range: 0.5-5m radial, adjustable from 10-100%. Time control 1second to 15minutes in 8different levels. Daylight detection with 5brightness levels and learning mode. Up to 9slave luminaires can be operated with one master luminaire (max. up to 150W / 230W). Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: white Diameter: 360mm Height: 100mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 20W Rated luminous flux: 1900lm Luminous efficiency: 95lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	20 W	CRI	80
Total flux	1900 lm	LOR	100%
Luminous efficacy	95 lm/W	ULOR	11%
		Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in

Diameter: 14.17 in

Adjustability

Fixed

Electric

System power: 20 W

Protection

IP: 40

IK: 10