


Product data sheet

NADJA I (W. SHIELD ON SIDE FACING BUILDING OPAL ATTACHMENT)
9.870.1052.26
LEIPZIGER LEUCHTEN



Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Metal halide lamp			
Nominal lamp power	100 W	LOR	84%
Lamp flux	10000 lm	Total flux	8440 lm
Luminous efficacy	73 lm/W	Total power	115 W
CCT	3000 K		
CRI	90		

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.69 in
Width: 12.20 in
Height: 3.86 in

Electric

System power: 115 W
Ballast: ECG
Appliance Class: I

Protection

IP: 55
Designation labels: CE

Other operating numbers

Ambient temperature range: -40...104°F