


Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, FULLY RECESSED ADJUSTABLE SPOTLIGHT
AF2103020-33-40_18W
SCHMITZ | WILA



alphabet focus LED 4000 K Recessed Luminaire, Light distribution direct Fully Recessed Adjustable Spotlight Product: AF2103020-33-40
Operating technology: independent driver required Light Technique highly precise lens technology (PLT), beam angle $\alpha = 9^\circ$ Light module 361° rotatable, with integrated rotation stop tilt range from $0\text{-}30^\circ$ constant colour temperature 4000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high- polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Drivers suitable for central battery Active cooling integrated flush with the heatsink (0,6 W; 14 dbA) fast and secure installation due to 4-point-fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety strap for easy installation Lamp Wattage: 18 W Colour Rendering Index: 90 Colour Temperature: 4000 K Luminaire Luminous Flux: 1210 Lm System Efficiency: 61 Lm/W Half-peak Divergence α : 9° Number Luminaires LZ: 0.09 Connector: Screw Connector, 3 x 1.5 mm² Reflector Size: Q10 Length: 127 mm Width: 127 mm Cut-out length: 120 mm Cut-out width: 120 mm Overhang OH: 115 mm Installation Depth RD: 200 mm Total Weight: 1.1 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF2103020-33-40_18W

Light output 1



1 x General service incandescent lamp

Nominal lamp power	20 W	LOR	100%
Lamp flux	1210 lm	Total flux	1210 lm
Luminous efficacy	60 lm/W	Total power	20 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.00 in
Width: 5.00 in
Height: 7.87 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 20 W
Appliance Class: II

Protection

IP: 20