


Product data sheet

SMART CAKE 160 IP55 LED GE 3000K FLOOD BLACK STRUC
13004732
MODULAR




Soft light Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


Light output 1




1 x LED			
Nominal lamp power	36.3 W	LOR	79%
Lamp flux	4095 lm	Total flux	3224 lm
Luminous efficacy	89 lm/W	Total power	36.3 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	30.8 W	LOR	79%
Lamp flux	3541 lm	Total flux	2788 lm
Luminous efficacy	91 lm/W	Total power	30.8 W
CCT	3000 K		
CRI	90		




1 x LED			
Nominal lamp power	23.5 W	LOR	79%
Lamp flux	2853 lm	Total flux	2247 lm
Luminous efficacy	96 lm/W	Total power	23.5 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	16 W	LOR	79%
Lamp flux	2095 lm	Total flux	1650 lm
Luminous efficacy	103 lm/W	Total power	16 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	49.7 W	LOR	79%
Lamp flux	5296 lm	Total flux	4170 lm
Luminous efficacy	84 lm/W	Total power	49.7 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	42 W	LOR	79%
Lamp flux	4600 lm	Total flux	3622 lm
Luminous efficacy	86 lm/W	Total power	42 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 4.76 in

Weight: 0.98 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W

Appliance Class: II

Protection

IP: 55