
# Product data sheet

LESS IS MORE 27 312177.0045.1.76

RZB








Series: LESS IS MORE 27 Recessed ceiling and wall luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. High polish aluminium micro grid. Perfect for office areas (UGR < 19) and environments with computer screens in accordance with EN 12464-1. Suitable for recessed ceiling mounting, wall (recessed). External driver with connecting cable. Colour: silver, matt (approx. RAL&#160;9006) Length: 1014&#160;mm Width: 38&#160;mm Height: 2&#160;mm Cut-out length: 1006&#160;mm Cut-out width: 30&#160;mm Recess height: 45-60&#160;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 82 System power: 25&#160;W Rated luminous flux: 2350&#160;lm Luminous efficiency: 94&#160;lm/W Control gear: Voltage converter, DALI dim. Protection class: II Type of protection: IP&#160;20

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25 W	CRI	80
Total flux	2350 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	25 W

# Mounting mode

Ceiling recessed

# Shape and measurements

Length: 1.50 in Width: 39.92 in Height: 0.08 in

#### Adjustability

Fixed

#### Electric

System power: 25 W

### Protection

IP: 20