


Product data sheet

LOUI 50
925320.0045.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Gerades Modulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Nur optional: Lichtbandsystem vorbereitet für Seilabhängung! Colour: silver, matt (approx. RAL;9006) Length: 1401;mm Width: 57;mm Height: 75;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 34;W Rated luminous flux: 4050;lm Luminous efficiency: 119;lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP;20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34 W	CRI	80
Total flux	4050 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	34 W

Mounting mode

Ceiling mounted

Electric

System power: 34 W

Shape and measurements

Length: 2.24 in
Width: 55.16 in
Height: 2.95 in

Protection

IP: 20
IK: 03

Adjustability

Fixed