

# Product data sheet


NADJA VII (1-ARMED BEADED)  
9.876.3162.86  
LEIPZIGER LEUCHTEN



IP  
55

Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711  
Luminaires generally compensatet


## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	39 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	5302 lm
Total power	137 W



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	35 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	3119 lm
Total power	89 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

## Electric

System power: 89-137 W

## Protection

IP: 55