


Product data sheet

AMEDH L30
AMENITY DECORATIVE LED HALO
DEXTRA



Amenity Decorative Halo LED - IP40, IK08 Circular surface mounted luminaire, with soft halo effect, white polycarbonate bulkhead, opal polycarbonate diffuser available with various decorative rings. Options: LE3 - Lithium Emergency (238 lumens) LS3 - Lithium Selftest LA3 - Lithium Autotest A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* S - Switch Dimming D - Digital Dimming (DSI) R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* R25W - Reacta-Wave Wireless sensor DALI R25WE - Reacta-Wave Wireless sensor On/Off *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off. AMED SRB - Amenity semi recessing kit (330mm cut out) AMED AWR - Amenity decorative angled white ring AMED ACR - Amenity decorative angled chrome ring AMED ABR - Amenity decorative angled brass ring NL - Night Light (not available with Emergency version)

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19.7 W	CRI	80
Total flux	2345 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	6%
		Total power	19.7 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.12 in
Diameter: 13.78 in

Adjustability

Fixed

Electric

System power: 19.7 W
Ballast: ECG

Protection

IP: 40
IK: 08
Designation labels: CE