

# Product data sheet


GAA GALLEONAIRE LED  
GAA-AF-08-LED-U-5WQ-8030-800  
COOPER LIGHTING



IP  
47

Choice of 16 high-efficiency, patented AccuLED Optics™, 3,400 - 61,800 lumens, up to 131 lp/W, Standard in 4000K CCT, 70 CRI, optional 2700K, 3000K, 5000K and 6000K, -40°C to 40°C operating range, 120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation, IP66 rated housing and LED Light Squares, Thermally conductive polymer heatsink for up to 22% weight reduction, Pole, mast-arm or wall-mounted configurations, 3G vibration rated, Five-year warranty

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 334 W    | CRI         | 80     |
| Total flux         | 33012 lm | LOR         | 100%   |
| Luminous efficacy  | 99 lm/W  | Total power | 334 W  |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 0.39 in  
Diameter: 6.00 in

## Adjustability

Fixed

## Electric

System power: 334 W

## Protection

IP: 47