Product data sheet

REKTOR RECESSED LED 3000K MEDIUM GE WHITE STRUC


12822009





Guiding the way around your space Rektor is a surprising fixture, as it is highly directional despite the super-sleek housing. This makes it a perfect example of accent lighting. Its extensive adjustability and metal colour accent on the housing make it a genuine must-have. Rektor is also handy for highlighting a wall or specific object. Designed in cooperation with Couvreur-Devos.

Light output 1



1 x LED			
Nominal lamp power	11 W	LOR	86%
Lamp flux	1046 lm	Total flux	899 lm
Luminous efficacy	82 lm/W	Total power	11 W
ССТ	3000 K		
CRI	90		
1 1 50			
1 x LED	10.05 \\\		0.604
Nominal lamp power	16.25 W	LOR	86%
		T , 10	1000 lm
Lamp flux	1434 lm	Total flux	1233 lm
Lamp flux Luminous efficacy	1434 lm 76 lm/W	Total flux Total power	1233 IM 16.25 W

Mounting mode	Electric	
Ceiling mounted	System power: 11-16.25 W	
Shape and measurements	Protection	
Length: 3.07 in	IP: 20	
Width: 3.07 in		

Created by luminaires.dialux.com (19 May, 2024)

Height: 4.29 in Adjustability Rotatable, Tiltable