


# Product data sheet

COMPASS  
03.3538/QT-12/50W/35W/20W/64°  
FLOS




Luminaire for halogen and high-pressure discharge lamps. Recessed body in black-painted metal. Die-cast aluminium alloy, powder-coated closing ring. Die-cast aluminium lamp support with heat dissipating element. Black thermoplastic anti-glare ring, 4 mm tempered glass cover. Stainless steel fixing brackets

## Light output 1




### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	20 W	Socket	E27
Lamp flux	300 lm	LOR	55%
Luminous efficacy	8 lm/W	Total flux	164 lm
CCT	2756 K	Total power	20 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gy6.35
Lamp flux	600 lm	LOR	55%
Luminous efficacy	9 lm/W	Total flux	328 lm
CCT	3000 K	Total power	35 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gy6.35
Lamp flux	910 lm	LOR	55%
Luminous efficacy	10 lm/W	Total flux	498 lm
CCT	3000 K	Total power	50 W
CRI	99		

## Mounting mode

Ceiling recessed

## Electric

System power: 20-50 W  
Appliance Class: III

### Shape and measurements

Height: 4.61 in

Diameter: 3.54 in

### Adjustability

Fixed

### Protection

IP: 43