
Product data sheet

LIGHT LINEAR 12 PT WALL AREA LUMINAIRES

LI-30012-LC-ME-W40 LIGMAN

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	53.5 W	CRI	80
Total flux	5894 lm	LOR	100%
Luminous efficacy	110 lm/W	Total power	53.5 W

Mounting mode

Pole top mounted, Wall mounted

Shape and measurements

Length: 19.88 in Width: 5.91 in Height: 3.15 in Weight: 7.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 53.5 W Voltage: 230 V AC Ballast: ECG Controller: Dimmable 1..10V, DALI Appliance Class: I

Protection

IP: 65 IK: 08 Surface temperature: 40°C