


Product data sheet

GINEVRA
1110100 QT32 100W
FLOS



• Outdoor/indoor floor lamp. • Configuration: vibrated and sandblasted concrete footing, extruded aluminium pole and white sanblasted polyethylene diffuser for a perfect light emission. • Double layer coating for high resistance to corrosion: The aluminium parts are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	E27
Lamp flux	1500 lm	LOR	98%
Luminous efficacy	15 lm/W	ULOR	53%
CCT	2800 K	Total flux	1467 lm
CRI	100	Total power	100 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Height: 23.62 in
Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 100 W
Appliance Class: I

Protection

IP: 65