

Product data sheet

NADJA II (WALL FITTING BEADED)

9.845.2036.06

LEIPZIGER LEUCHTEN




Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	78%
Lamp flux	3500 lm	Total flux	2729 lm
Luminous efficacy	44 lm/W	Total power	62 W
CCT	2000 K		
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	78%
Lamp flux	5600 lm	Total flux	4366 lm
Luminous efficacy	53 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 20.08 in

Diameter: 20.08 in

Design

Material impression: Matt

Glare protection

Glare protection: UGR < 19

Electric

System power: 62-83 W

Ballast: ECG

Controller: DALI

Protection

IP: 55

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...95°F