


Product data sheet

MONDANA-HE
551089.002.1
RZB




IP
65

IK
10

Series: Mondana Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: plastic (polycarbonate), microtextured finish. Diffuser fastening: screw fitting. Diffuser: plastic (polyethylene), opal, satin finish. With Gore-TM Protective Vents membrane valve as standard. Recessed housing: metal, powder-coated, for installation in cavity walls with 10-30 mm wall thickness. Available Colours: pure white (RAL 9010) Type of Installation: Recessed ceiling mounting, Wall (recessed) Dimensions: D 280, H 70 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 650lm System power: 9W Beam Angle: 117° Unified Glare Ratio: 16,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	650 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	24%
		Total power	9 W

Mounting mode

Wall recessed

Electric

System power: 9 W

Shape and measurements

Height: 4.17 in
Diameter: 11.02 in

Protection

IP: 65
IK: 10

Adjustability

Fixed

Design

Color of housing: White