

# Product data sheet


PETRA PIV  
9.883.5497.41  
LEIPZIGER LEUCHTEN



IP  
44

Feeder pillar with light designed to supply power to markets, squares and parks and gives personal safety and visual amenity at the same time  
Petra P IV: Glazed on one side Petra P VI: Glazed on two sides - Luminaire glazing made of UV-stabilised impact resistant opal polycarbonate. - Luminaire body and head made of hot-dip galvanised steel and available powder coated in any RAL or DB colour as required - One gear tray includes all electrical components - For lamp change luminaire head completely detachable with tool - Luminaire tube with door - Earthing screw on post - Inclusive power unit, IP 44: •1x protection-socket 230 V, 50 Hz/16A •1x CEE-socket 16A 5p 400V •1x LS 16A 3p-C •1x LS 16A 1p-C •1x FI - 40/4/0,03A - Operates with open supply door - Including a three-edge-key M6

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	26 W	LOR	24%
Lamp flux	1800 lm	ULOR	12%
Luminous efficacy	16 lm/W	Total flux	439 lm
CCT	2899 K	Total power	28 W
CRI	90		

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 43.31 in  
Diameter: 6.69 in

## Electric

System power: 28 W

## Protection

IP: 44