Product data sheet

SHARP RECESSED TRIM 8X 24W 927 WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK AF14801+AF95204

ARTEMIDE









SHARP RECESSED TRIM 8X 24W 927 WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	2.75 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	2.75 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	2.75 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total pov	wer 2.75 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	2.75 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	2.75 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total power	2.75 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	2.75 W	CRI	90
Total flux	174 lm	LOR	100%
Luminous efficacy	63 lm/W	Total powe	er 2.75 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.17 in Width: 12.28 in Height: 1.72 in

Adjustability

Fixed

Electric

System power: 22 W

Protection

IP: 20