## Product data sheet

GUSTAV I (WALL FITTING) 9.744.2032.07

LEIPZIGER LEUCHTEN








Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



## 1 x High pressure sodium vapour lamp

1 X riight pressure souldn't vapour lamp			
Nominal lamp power	70 W	LOR	54%
Lamp flux	5600 lm	ULOR	11%
Luminous efficacy	36 lm/W	Total flux	3004 lm
CCT	2000 K	Total power	83 W
CBI	25		

Mounting mode

Wall mounted

Shape and measurements

Height: 9.84 in Diameter: 9.84 in

Design

Material impression: Matt Color of housing: White Electric

System power: 83 W Ballast: ECG

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F