


# Product data sheet

KORA PI (POLLERLEUCHTE MIT KÜK)  
9.821.5497.11  
LEIPZIGER LEUCHTEN



Bollard- particularly (designed or constructed or built) in order to give orientation and light to entrances and ways in parks and gardens. - Light exit: Kora P I and P II on 4 sides Kora P III on 1 or 3 sides - Impact-resistant opal polycarbonate cube, UV-stabilized - Special steel luminaire body and unit carrier, available painted in DB 703 (Iron Glimmer) or in any RAL or DB colour without surcharge, or ground and passivated - Adapter jack connection - Luminaire body completely detachable for lamp replacement, opens with tool - Kora P I with open incl. cable joint box for 2 cables 5 x 10 mm<sup>2</sup> or cables 5 x 6 mm<sup>2</sup> Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711

## Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	26 W	LOR	18%
Lamp flux	1800 lm	ULOR	10%
Luminous efficacy	12 lm/W	Total flux	325 lm
CCT	2899 K	Total power	28 W
CRI	90		

## Mounting mode

Standing / Bollard, Ceiling mounted

## Shape and measurements

Length: 4.72 in

Width: 4.72 in

Height: 35.43 in

## Design

Material impression: Matt

Color of housing: White

## Electric

System power: 28 W

Ballast: ECG

Controller: DALI

## Protection

IP: 65

Designation labels: CE

## Other operating numbers

Ambient temperature range: 5...95°F