Product data sheet

ECHO GRAPHITE 360LM 2700K RA>80 TRAILING EDGE DIMMING 7021986236835

SG ARMATUREN










Attractive, square wall luminaire that can be installed both indoors and outdoors. Attractive light both up and down or only down. Made of diecast powder-coated aluminium. Glass diffuser. Smart wall fittings with connector for the lamp, two inputs/outputs for wires, option of both visible and concealed cabling, and loopable quick clips. Light distribution Direct/Indirect Light technic LED (exchangeable) GU10 9W (2 x 4.5W) 2700K Ra>80 SDCM 4 L70/B50 >40,000 hrs Ta=25°C Control/Dimming Trailing edge dimming Protection Class II IP54 IK07 Energy and approvals A CE Materials and finish Housing: Aluminium Colour: Graphite Optics: Tempered glass Mounting/Connection Surface, Outdoor Screwless terminal block

Light output 1



1 x LED		
Nominal lamp power		
Lamp flux		
Luminous efficacy		
CCT		
CRI		

9 W	LOR
360 lm	ULOR
40 lm/W	Total flux
2700 K	Total powe
80	

3	100%
OR	50%
al flux	360 lm
al power	9 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.54 in Width: 5.79 in Height: 8.46 in

Adjustability

Fixed

Electric

System power: 9 W Appliance Class: II

Protection

IP: 54 IK: 07