


# Product data sheet

VEKTER 4 BOLLARD  
VK-10011-ME-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Integral control gear

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4032 K |
| Nominal lamp power | 19.7 W   | CRI         | 80     |
| Total flux         | 2300 lm  | LOR         | 100%   |
| Luminous efficacy  | 117 lm/W | Total power | 19.7 W |

## Light output 2 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4032 K |
| Nominal lamp power | 19.7 W   | CRI         | 80     |
| Total flux         | 2300 lm  | LOR         | 100%   |
| Luminous efficacy  | 117 lm/W | Total power | 19.7 W |

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 26.38 in  
Width: 10.24 in  
Height: 47.24 in  
Weight: 11.2 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 39.4 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C