Product data sheet

NADJA I (WALL FITTING BEADED) 9.840.3162.06


LEIPZIGER LEUCHTEN



Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

IP **€** ₹

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR	78%		
Lamp flux	6800 lm	Total flux	5302 lm		
Luminous efficacy	39 lm/W	Total power	137 W		
CCT	3400 K				
CRI	54				

	HT
	44
	$\langle \rangle$
	\times
XH	\succ
XH	\geq

y vapour lamp		
80 W	LOR	78%
4000 lm	Total flux	3119 lm
35 lm/W	Total power	89 W
3400 K		
54		
	4000 lm 35 lm/W 3400 K	80 W LOR 4000 lm Total flux 35 lm/W Total power 3400 K

Mounting mode Wall mounted

Shape and measurements Height: 20.08 in

Diameter: 20.08 in

Electric System power: 89-137 W

Protection

IP: 55 Designation labels: CE, F