


Product data sheet

LOUI 50
925364.0045.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50 system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Colour: silver, matt (approx. RAL 9006) Length: 1961 mm Width: 71 mm Height: 1.5 mm Cut-out length: 1968 mm Cut-out width: 60 mm Recess height: 100 mm Luminaire: recess height: 75 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 48 W Rated luminous flux: 6200 lm Luminous efficiency: 129 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	48 W	CRI	80
Total flux	6200 lm	LOR	100%
Luminous efficacy	129 lm/W	Total power	48 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 77.20 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 48 W

Protection

IP: 20
IK: 03