



Product data sheet

SIRIUS 1200 - CC SUSPENSION
1232-K-2-688-XX
UNILAMP




Description A brand new linear light family features various mounting application types including In-ground walk over, wall mounted, wall recessed, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	8.6 W	LOR	100%
Lamp flux	340 lm	Total flux	340 lm
Luminous efficacy	40 lm/W	Total power	8.6 W
CCT	4000 K		
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	9 W	LOR	100%
Lamp flux	238 lm	Total flux	237 lm
Luminous efficacy	26 lm/W	Total power	9 W
CCT	0 K		
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	8.2 W	LOR	100%
Lamp flux	701 lm	Total flux	700 lm
Luminous efficacy	85 lm/W	Total power	8.2 W
CCT	8000 K		
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	6.8 W	LOR	100%
Lamp flux	340 lm	Total flux	340 lm
Luminous efficacy	50 lm/W	Total power	6.8 W
CCT	0 K		
CRI	-36		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 46.79 in

Width: 2.44 in

Height: 22.13 in

Adjustability

Fixed

Electric

System power: 32.6 W

Appliance Class: III

Protection

IP: 67

IK: 07